



ABRASION/MECHANICAL

ROUNDIT® 2000 LX

PROJECT DATASHEET

Product Highlights

- Operating Temperature:
- 60°C to + 200°C
(-76°F to 392°F)
- Extremely lightweight
- FAR Part 25
- Halogen-free
- Oil and water repellant
- Abrasion and cut-through resistant
- Self-wrapping design

Installation Features

- Easy to apply and remove
- Ideal for reworking components without disconnecting them
- Tracer indicating the maximum operating diameter



Our manufacturing sites are certified ISO 9000, QS 9000 or ISO/TS 16949 and ISO 14001

RI2000LX_08052008



ROUNDIT® 2000 LX is a self-wrapping sleeve used for abrasion protection of wire and cable bundles. It is woven from a blend of PPS (polyphenylene sulfide) multifilaments with an oil and water repellant treatment. The wrappable construction was designed in order to minimize weight while maintaining 100% coverage, resulting in an optimized combination of lightweight materials and abrasion resistance.

The self-wrapping feature of ROUNDIT 2000 LX allows for quick and easy installation and removal of the product for assembly and maintenance. This product is rated to 200°C and is non-halogenated.

ROUNDIT 2000LX has many applications in the aeronautical and defense industries due to its extremely lightweight and halogen-free construction.



As an added benefit, the patented ROUNDIT® Tool will help improve installation time and is designed to install ROUNDIT® products on cable and wire configurations.