



## Product Highlights

- Operating temperature up to +200°C (+392°F)
- Excellent radiant and convective heat protection
- Self-wrapping design allows for break-outs
- Lightweight, flexible & easy to install
- Fluid and chemical resistant

## Typical Applications

- Cooling Lines
- Copper Data Cables
- Server Rack Routing
- Thermal Runaway Protection

**Therm-L-Wrap™ 26** is a self-wrapping, reflective sleeve designed to provide thermal protection for both radiant and convective heat applications. Composed of a woven fiberglass base fabric and a lamination of aluminum foil, the product can withstand convective heat soaks up to +200°C (+392°F) and simultaneously protect critical components from radiant or reflected heat.

The self-wrapping design of Therm-L-Wrap 26 allows for quick and easy installation with a self-sealing adhesive reinforcement for permanent closure. The adhesive strip acts as a barrier to dirt and fluids while maintaining the full integrity of the finished aluminized sleeve.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)



Office: 866-956-8323  
Email: [contact@titanelectronics.com](mailto:contact@titanelectronics.com)  
Website: [www.titanelectronics.com](http://www.titanelectronics.com)  
ISO 9001:2015 / AS9100D

**BentleyHarris®**  
Protection Products