

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Expando FR Manufacturer:

Federal-Mogul Corporation 26555 Northwestern Highway

Southfield, MI 48033

MSDS# BH-005 24hr Emerg # (Infotrac): 1-800-535-5053

International: 001-352-323-3500 Non-Emerg #: 248-354-9844

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Bentley-Harris Expando FR sleeving is a tough, lightweight product used to oversleeve and protect cable assemblies, hoses, and wire harnesses. Made of braided flame retardant polyester monofilaments, Expando FR increases cut-through strength and abrasion resistance of electrical and thermal insulating surfaces. It is UL recognized as a VW-1 component.

Although several of the ingredients used to formulate this product may be hazardous in the raw state, the manufacturing process results in a solid, infusible form, binding and otherwise, rendering the product inert. The constituents identified below may be present in quantities greater than 1% (0.1% for carcinogens) that may be release from the product by overheating, burning, machining, abrading, or riveting.

This information provides the minimum criteria for safe usage and handling of this product. Companies using this product should develop their own occupational health program to protect employees from injury or adverse health effects.

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV
Thermoplastic Polyester	None Established	<30	None Established	None Established
Antimony Trioxide	1327-33-9	<30	0.5 mg/m³	None Established (A2)
Organic Flame Retardant	None Established	<45	None Established	None Established

A2: Categorized by ACGIH as Suspected Huam Carcinogen; there is limited evidence of carcinogenicity in humans and sufficient ecidence of carcinogenicity inexperimental anim as with revelance to humans

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Shipped material is not considered hazardous, but operations (e.g., overheating, burning, machining, abrading, or riveting) that can create airborne dust should be avoided.

POTENTIAL HEALTH EFFECTS

Inhalation: Dust from abnormal abrasion or vapors from heating to greater than 300°C can cause irritation.

Skin: Molten material can cause thermal burns.

Eye: Solid or dust particle may cause irritation or corneal injury.

Ingestion: Not a probable route of entry.

Revised: 04/27/2005 Page 1 of 5

POTENTIAL HEALTH EFFECTS (continued)

Carcinogenicity:

COMPONENT NTP IARC OSHA

Thermoplastic Polyester

No No No

Antimony Trioxide

No No No

Organic Flam Retardant

No No No

Symptoms and Effects of Exposure to Selected Individual Components

ANTIMONY TRIOXIDE

Inhalation – No serious health risks reported from exposure other than a possible change in blood pressure. Prologned exposure may cause irritation of the nose, throat and mouth.

Other hazards – Skin or eye contact may result in coughing, dizziness, headache, nausea, vomiting, diarrhea, stomach cramps and insomnia.

SECTION 4: FIRST AID MEASURES

Inhalation: Move to fresh air. Seek medical attention.

Eye Contact: Rinse thoroughly with ample amounts of water for 15 minutes. Seek medical attention.

Skin Contact: Wash thoroughly with soap and water. If molten material falls on skin, do not attempt to

remove material; cool immediately with water. Seek medical attention.

Ingestion: Seek medical attention.

Revised: 04/27/2005 Page 2 of 5

SECTION 5: FIRE FIGHTING MEASURES

This product is inherently flame resistant, but may ignite at temperature exceeding 600°C in an oxygenenriched atmosphere.

Flashpoint: N/A LEL: N/A UEL: N/A Autoignition Temperature: N/A

Extinguishing Media: Use media suitable for surrounding fire. Product is a flame retardant.

Unusual Fire and Explosion Hazards: Toxic vapors can be emitted under fire conditions.

Special Fire Fighting Procedure: Wear self-contained breathing apparatus when extinguishing.

Hazardous decomposition products are generated in fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Scrap monofilament may present a slipping hazard. Sweep up and dispose of according to all federal and state disposal procedures. If dust is generated during machining, abrading or riveting, remove dust by vacuuming or wet mopping. Do not use compressed air to blow dust from surfaces.

SECTION 7: HANDLING AND STORAGE

Do not heat to greater than 200°C. Avoid breathing fumes at elevated temperatures. If dust is generated while shipping product, remove dust by vacuuming or wet-mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Any operation which may produce dust, including machining, grinding, riveting, or

abrading this product, should be adequately exhausted to prevent inhalation of dust.

Respiratory Protection: Use a NIOSH-approved respirator if there is a potential for exposure to dust, vapor,

or fume exceeding PELs or TLVs. (See 29 CFR 1910.134, OSHA Respiratory

Protection Standard.)

Skin Protection: If skin irritation occurs, gloves and other protective garments may be worn.

Eyes: Wear safety glasses or goggles, as necessary, if dust exposure is possible.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:N/AVapor Pressure:N/AMelting Point:240 - 250°CVapor Density (air = 1):N/ApH:N/A% Volatile:N/ASpecific Gravity:1.5 g/ccEvaporation Rate:N/A

Water Solubility: Insoluble Form, color and Odor: Solid, black or white and odorless

Revised: 04/27/2005 Page 3 of 5

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Incompatibility Oxidizing agents, acids and bases

(Materials/Conditions to Avoid):

Hazardous Polymerization: Will not polymerize

Decomposition Products: Avoid exposing to temperatures to greater than 300°C for prolonged

periods of time. At this temperature, thermal decomposition starts to occur

producing such by-products as carbon monoxide, carbon dioxide,

hydrogen bromide and bromine.

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation: Refer to Section 3

Skin: Refer to Section 3

Eye: Refer to Section 3

Ingestion: Refer to Section 3

Acute: None known

Chronic: None known

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Federal and state law regulates disposal of scrap material or dust as solid waste; disposal must be in accordance with federal and state laws. Contact local regulatory agencies for guidance.

SECTION 14: TRANSPORTATION INFORMATION

Proper Shipping Name: Not regulated

Hazard Class:NoneIdentification Number:NonePacking Group:N/AShipping Label:NoneAdditional Marking Requirement:None

Revised: 04/27/2005 Page 4 of 5

SECTION 15: REGULATORY INFORMATION

U.S. TSCA: All chemicals used in the manufacture of this product are listed on the

U.S. Toxic Substances Control Act (TSCA) Inventory

California Proposition 65: This product does not contain ingredients known to the State of

California to cause cancer, birth defects or other reproductive effects.

SARA Title III - Section 313

Supplier Notification:

This product does not contain chemicals subject to SARA Title III/CERCLA "reportable quantities" (RQs) and/or "threshold planning quantities" (TPQs) and/or are classified as "Toxic Chemicals" under the Emergency Planning and Community Right-To-Know Act

(EPCRA) of 1986 and 40 CFR 372.

RCRA Hazardous Waste Code: Not Available

CERCLA Hazardous Substances: Not Available

OSHA: Not Available

WHMIS Classification: Not Available

SECTION 16: OTHER INFORMATION

Abbreviations:

CAS No.: Chemical Abstract Services Number

OSHA PEL: U.S. Occupational Safety and Health Administration Permissible Exposure Limit

ACGIH TLV: American Conference of Governmental Industrial Hygienists Threshold Limit Value (2004)

N/A: Not Applicable

IARC: International Agency for Research on Cancer

NTP: National Toxicology Program

The information and recommendations stated above are taken from sources believed to be accurate as of the date of this revision. Federal-Mogul makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereof.

This MSDS should not be used as a complete or accurate summary of the content of this product. For specific information on brand names, manufacturers, or quantities, please refer to product specification documents, wherever available.

Revised: 04/27/2005 Page 5 of 5